



AR20 Red General Purpose Air/Water



Application:

Air, water, agricultural spray solutions, and other diluted chemicals. Good resistance to heat, abrasion, and weathering.

Construction:

Tube - Black, limited oil resistant synthetic rubber

Reinforcement - Synthetic yarn

Cover - Smooth, red, abrasion, weather, and ozone resistant rubber

Branding - FLEXTRAL AR20-100 1" (25.4mm) GENERAL PURPOSE AIR/WATER 300 PSI MAX WP

Temperature Range:

-29°C to +80°C (-20°F to +180°F)

Part No.	I.D. Inches	O.D. Inches	Max W.P. PSI	Weight lbs / ft	Reel Lengths
AR20-025	¼	0.53	300	0.13	600'
AR20-038	⅜	0.70	300	0.21	600'
AR20-050	½	0.84	300	0.27	600'
AR20-063	⅝	0.98	300	0.34	400'
AR20-075	¾	1.15	300	0.46	400'
AR20-100	1	1.47	300	0.68	250'
AR20-125	1¼	1.73	300	0.84	200' Coils
AR20-150	1½	2.09	300	1.24	200' Coils
AR20-200	2	2.64	300	1.74	200' Coils

AR20 Red General Purpose 300 PSI Assemblies



Part No.	Hose Size & Length	End 1	End 2	Attaching Method
AR20-025MMXF025-BR	¼" x 25'	¼" M-NPT	¼" M-NPT	Crimp
AR20-025MMXF050-BR	¼" x 50'	¼" M-NPT	¼" M-NPT	Crimp
AR20-038M2525MXF025-BR	⅜" x 25'	¼" M-NPT	¼" M-NPT	Crimp
AR20-038M2525MXF050-BR	⅜" x 50'	¼" M-NPT	¼" M-NPT	Crimp
AR20-038M2525MXF100-BR	⅜" x 100'	¼" M-NPT	¼" M-NPT	Crimp
AR20-038MMXF050-BR	⅜" x 50'	⅜" M-NPT	⅜" M-NPT	Crimp
AR20-038MMXF100-BR	⅜" x 100'	⅜" M-NPT	⅜" M-NPT	Crimp
AR20-050MMXF050-BR	½" x 50'	½" M-NPT	½" M-NPT	Crimp

*Call for additional fittings, lengths and assemblies.