

HIGH-PERFORMANCE INTUMESCENT FIRESTOP SEALANT FS-ONE MAX

Product description

- Intumescent (expands when exposed to fire) firestop sealant that helps protect combustible and non-combustible penetrations for up to 4 hours fire rating

Applications for use

- For effectively sealing most common through penetrations in a variety of base materials
- For use on concrete, masonry and drywall
- Mixed and multiple penetrations
- Metal pipe penetrations: copper, steel and EMT
- Insulated metal pipe penetrations: steel and copper
- Plastic pipe penetrations: closed or vented

Advantages

- US-produced: "Buy American" compliant
- One product for a variety of common through penetrations
- Cost-effective, easy-to-use solution
- Water-based and paintable
- Industry-leading VOC results
- Ethylene glycol-free

Installation instructions

- See Hilti literature or third-party listings for complete application and installation details




Technical Data*

Chemical basis	Water-based acrylic dispersion
Approx. Density	84.3 lb/ft ³
Color	Red
Approx. cure time¹⁾	2mm / 3 days
Application temperature range²⁾	35°F to 104° (1.5°C to 40°C)
Temperature resistance range	-4°F to 212°F (-20°C to 100°C)
Storage Temperature	35°F to 77°F (1.5°C to 25°C)
Tack free time	20mins (@ 73°F / 50% rel. humidity)
Shelf life	18 months
Temperature resistance range	-4°F to 212°F
Mold and mildew performance	Class 0 (ASTM G21-13)
Mold and mildew resistant	Yes
Expansion ratio (unrestricted, up to)	1:5
Paintable	Yes
Chemical resistance	Yes
Electrical resistance	Yes
FBC compatible (Lubrizol)	Yes
Intumescent	Yes
W-rating	Yes
M-rated	Yes
LEED VOC (input)	9 g/L
LEED V4 Compliant	Yes (CDPH v1.2-2017)
STC rating (ASTM E90)	62 (relates to specific construction)
Movement	±7.5%
Surface burning characteristics (ASTM E 84-14)	Flame Spread: 0 Smoke Development: 10
California State Fire Marshal approval	CSFM Listing 4485-1200:0108 for FS-ONE MAX Intumescent Firestop Sealant
Tested in accordance with	ASTM G21, ASTM E 90, CAN/ULC-S115, UL 1479, ASTM E 814 , ASTM E84

Order Information

Designation	Qty per package	Item number
FS-ONE MAX 10oz tube (1 case)	12x Firestop sealant FS-ONE MAX 10 oz cartridge	3530249
FS-ONE MAX 20oz foil (1 case)	25x Firestop sealant FS-ONE MAX 20 oz foil	3530250
FS-ONE MAX 10 oz cartridge	1x Firestop sealant FS-ONE MAX 10 oz cartridge	2101531
FS-ONE MAX 5 gallon pail	1x Firestop sealant FS-ONE MAX 5 gallon pail	2101533



Intertek



Chemical resistant



Mold and mildew resistant



Volume per unit:

- Caulk tube = 10.5 fl. oz (18.9in³)
- Foil = 600ml (36.4in³)
- Pail = 5gal (1,155in³)

1) At 75°F (24°C) and 50% relative humidity

2) For ambient and surface temperatures between 10°F (-12°C) and 35°F (1.5°C), the following conditions must apply:

- Substrate surfaces are clean and dry (e.g. free of dust, rust, grease, oil, dew, frost, ice, moisture, etc);
- Product maintained above 50°F (10°C) for a minimum of 24 hours prior to application;
- Product will not cure at ambient temperatures below 32°F / 0°C