



model 5017LF

Drinking Faucet

FEATURES & BENEFITS

QUALITY

Bubbler is pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and added peace of mind.

BUBBLER VALVE

Polished stainless steel cartridge valve which allows for top access stream adjustment as well as cartridge and strainer access, and is designed with a shielded, anti-squirt orifice that provides a steady sanitary source of water.

OPTIONS

For more information, visit www.hawsc.com or call (888) 640-4297.



SPECIFICATIONS

Model 5017LF deck mounted bubbler valve shall include a polished chrome-plated brass base with integral cartridge valve with stream flow regulation, polished chrome-plated brass bubbler head, and 1/2" O.D. (1.3 cm) slip-joint inlet.


APPLICATIONS

Perfect for either public or private indoor settings, the 5017LF is a great fit in areas where a countertop is in close proximity to a sink/bowl. Specifically, this type of deck mounted drinking faucet may be placed in settings such as: schools, classrooms, laboratories, and other facilities where the need for a deck mounted sink/faucet is present. This product meets ADA requirements, and Haws manufactures drinking fountains, faucets and electric water coolers to be lead-free by all known definitions including NSF/ANSI/CAN 61- Section 9, NSF/ANSI/CAN 372, California Proposition 65, and the Federal Safe Drinking Water Act. Product is compliant to California Health and Safety Code 116875 (AB 1953-2006), and NSF/ANSI/CAN 61: Q ≤ 0.5.



NOTES:

1. WHEN INSTALLING THIS UNIT, LOCAL, STATE OR FEDERAL CODES SHOULD BE ADHERED TO FOR INSTALLATION PARAMETERS (DIMENSIONS, LOCATIONS) AND WASTE AND SUPPLY REQUIREMENTS OTHER THAN SHOWN.
2. FLOW ADJUSTMENT: REMOVE HEX NUT AND BUTTON. ADJUST FLOW WITH SCREWDRIVER; CLOCKWISE FOR MORE FLOW, COUNTERCLOCKWISE FOR LESS. IF DESIRED FLOW IS NOT OBTAINED, MAKE SURE SCREWDRIVER STOP IS FULLY OPEN. REINSTALL BUTTON AND HEX NUT.



MOUNTING HOLE

SCALE: 2/1

Haws Corporation		INFO FAX : 1-888-FAX-HAWS (1-888-329-4297)	
1455 Kleppe Ln, Sparks, NV, 89431		Phone: 775-355-4715	
Haws P9, Bochweg 3, CH-3401, Burgdorf, Switzerland		Fax: 775-355-7424	
Haws Wfg Pte Ltd 74, Sungei Kadut Loop, Singapore 729531		Fax: 65-6753-7512	
e-mail: Haws@hawsco.com		Fax: 14148000	
www.hawsco.com		Fax: 14148000	
MODEL(S): 5017LF		DATE: 07/99	
INFO FAX DOC # 250173		DATE: 07/99	
DRAWING TYPE: INSTALLATION/FABRICK		DATE: 07/99	
SCALE: 1:3		DATE: 07/99	
SIZE: A		SHEET: 1 OF 1	