



Product Family
Max Single-Use Earplug

Highest attenuation in single-use earplugs

[Learn more about our products at howardleight.com](http://howardleight.com)



Product Numbers & Ordering Information

	Product Numbers	Details
	MAX-30	Max - corded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
	MAX-1	Max - uncorded SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
	MAX-LS4	Max - uncorded bulk refill for Leight Source 400 SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.
	MAX-1-D	Max - uncorded bulk refill for Leight Source 500 SLC80 26dB Class 5. Approved to AS/NZS 1270:2002.

Overview

Key Features

- The world's most-used polyurethane foam earplug
- Bell shape delivers maximum in-ear comfort
- Contoured design easier to insert, resists tendency to back-out of ear canal
- Polyurethane foam enhances comfort, especially for long-term wear
- Smooth, soil-resistant closed cell-foam skin prevents dirt build-up
- Bulk refills for Leight Source 400 and Leight Source 500 Earplug Dispensers save time, waste and space

Recommended Industries/Use

- Agriculture
- Chemical
- Construction
- Fire Protection
- Forestry
- Government

Max Single-Use Earplug

Hazards • Enforcement • Manufacturing • Medical • Military • Mining • Municipal Services
• Oil and Gas • Pharmaceutical • Steel and Metals • Transportation • Utilities • Welding

Regulations

- 29 CFR 1910.95 - OSHA Occupational Noise Exposure (US)
- ANSI S3.19-1974 - Attenuation Test Protocol (US)
- Part II, (R.S.C. 1985, c. L-2) - Canada Labour Code
- Z94.2-1994 - Attenuation Test Protocol (CAN)
- 2003/10/EC - EU Hearing Directive
- 89/686/EEC - EC Directive/PPE
- Category II - EC Category/PPE
- EN 352-2:2002 - EU Standards
- NOHSC: 1007 (2000) - National Standard for Occupational Noise (AUS/NZ)
- NR 15 - Security and Health of Work, Annexes 1 and 2, n°3.214/1978 - Occupational Noise Regulations (BR)
- ANSI S12.6/1997 - Method B - Attenuation Test Protocol (BR)
- 9001:2008 - ISO

Historical Brand

Howard Leight

Specifications

Color

- Coral

Shape

- Bell

Material

- Polyurethane Foam

Packaging Options

- Polybag • Paper Bag • Bulk Refill for Leight Source 400 or Leight Source 500 Dispenser

Cord Options

- Uncorded • Polycord

NRR

- 33

Canada Class

- A(L)

SNR

- 37

SLC80

- 26 dB / Class 5

EU Certifications

- European Directives – 89/686/EEC
- EC Category PPE – Category II
- Standards – EN 352-2:2002
- EC Certification Number – 1219
- EC Attestation Number – 040366
- Laboratory – INSPEC
-

AUS Certifications

- Standardsmark License #1579

Max Single-Use Earplug

5. Removal – Gently twist earplug while slowly pulling in an outward motion for removal.
6. Acoustical Check – In a noisy environment, with earplugs inserted, cup your hands over your ears and release. Earplugs should block enough noise so that covering your ears with your hands should not result in a significant noise difference.

Additional Information

CARE + MAINTENANCE

- INSPECT – Inspect prior to fitting, examine your earplugs for dirt, damage or extreme hardness—discard immediately if compromised.
- DISCARD – For proper hygiene, discard Single-Use earplugs after use.
- HYGIENE – To maintain hygiene standards, Single-Use earplugs should be discarded at the end of every shift.

RELATED PRODUCTS