

Pipe/Tube Cutting & Preparation



No. 42-A



No. 44-S

4-Wheel Pipe Cutters

- Designed for work in areas where a complete turn is impossible.
- No. 42-A has a short handle for use in confined areas.
- Second handle on No. 44-S makes two-man leverage possible for large pipe sizes.
- Both equipped with four heavy-duty wheels.

Catalog No.	Model No.	Pipe Cutter Description	Pipe Capacity Nominal Size		Weight	
			in.	mm	lb.	kg
32870	42-A	Heavy-Duty 4-Wheel	3/4-2	20-50	6 3/4	3.1
32880	44-S	Heavy-Duty 4-Wheel	2 1/2-4	60-100	20	9.1



No. 202

Wide-Roll Pipe Cutter

- Featuring extra-wide rolls, this cutter is especially designed for use with power drives.
- The wide rolls provide for true tracking and cleaner cuts.

Catalog No.	Model No.	Pipe Cutter Description	Pipe Capacity Nominal Size		Weight	
			in.	mm	lb.	kg
32895	202	Heavy-Duty Wide Rolls	1/8-2	3-50	8	3.5

* Furnished with X-tra™ sharp wheel for up to 40% faster cutting.



Hinged Pipe Cutters

- Designed for rapid cutting of 2" through 12" steel pipe, heavy-wall steel pipe and cast-iron pipe.
- The 11 models operate with minimal cutter rotation as necessary for tight quarters.
- Second handle included for 466, 472 and 468 makes two-man leverage possible for large pipe sizes.

Catalog No.	Model No.	Pipe Cutter Description	Pipe Capacity Nominal Size		Weight	
			in.	mm	lb.	kg
74227	424-CI	For Cast/Ductile Iron	2-4	50-100	13 1/2	6.0
83080	466-S*	For Steel Pipe	4-6	100-150	28 1/2	13.0
83085	466-HWS*	For Heavy-Wall Steel Pipe	4-6	100-150	28 1/2	13.0
74685	466-CI	For Cast-Iron Pipe	4-6	100-150	28 1/2	13.0
83145	468-S*	For Steel Pipe	6-8	150-200	33	15.0
83150	468-HWS*	For Heavy-Wall Steel Pipe	6-8	150-200	33 1/2	15.2
74700	468-CI	For Cast-Iron Pipe	6-8	150-200	33 1/2	15.2
83165	472-S*	For Steel Pipe	8-12	200-300	41 1/2	19.0
83170	472-HWS*	For Heavy-Wall Steel Pipe	8-12	200-300	42	19.1
74710	472-CI	For Cast-Iron Pipe	8-12	200-300	42	19.1

* Furnished with X-tra sharp wheel for up to 40% faster cutting.



Three- and four-wheel pipe cutters should only be used when the cutter cannot be rotated completely around the pipe.