

RAYCLIC CONNECTION KIT



nVent RAYCHEM RayClic connection system is a simple, fast and reliable set of connection kits developed for select nVent RAYCHEM XL-Trace, IceStop and HWAT self-regulating heating cables. No heat guns or wire stripping are needed, because insulation displacement technology is used to make the electrical connection.

FEATURES & BENEFITS

Simple, fast, intuitive connection: no wire stripping or special tools needed

Lower total installed system cost, due to reduced installation time: cold applied, no heat guns or special tools needed

Reliable during long life: 10 year extended product warranty available, maintenance free

Cold applied, no heat guns needed, no special tools

SPECIFICATIONS

Connection Type Cold Applied

Voltage Rating 120 – 277 V

Current Rating 30 A

Max Exposure Temperature 150 °F

Color Grey

Table 1/1

Catalog Number	Item Name	Model
546349-000	RAYCLIC-X	X-Branch
233053-000	RAYCLIC-PC	Power Connection to One Heating Cable

Catalog Number	Item Name	Model
559871-000	RAYCLIC-S	Heating Cable/Heating Cable
014023-000	RAYCLIC-T	T-Branch
861247-000	RAYCLIC-PS	Power Connection to Two Heating Cables
804231-000	RAYCLIC-PT	Power Connection and T-Branch

For proper design and installation of a RayClic connection system, use the appropriate product design guide and the installation instructions included with the connection kit.

North America

Tel +1.800.545.6258
Fax +1.800.527.5703
thermal.info@nvent.com

Europe, Middle East, Africa

Tel +32.16.213.511
Fax +32.16.213.604
thermal.info@nvent.com

Asia Pacific

Tel +86.21.2412.1688
Fax +86.21.5426.3167
cn.thermal.info@nvent.com

Latin America

Tel +1.713.868.4800
Fax +1.713.868.2333
thermal.info@nvent.com



Our powerful portfolio of brands:
nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2021 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.
nVent reserves the right to change specifications without notice.