

CA Expansion Tanks

CAPACITY: 23 — 2,640 Gallons
(90 - 10,000 liters)

DIAMETER: 20" — 72"

HEIGHT: 29" — 160"

Field replaceable, heavy-duty butyl full acceptance rubber bladder removes easily for inspection.*

CX Expansion Tanks

CAPACITY: 8 — 92 Gallons
(29 - 171 liters)

DIAMETER: 14" — 24"

HEIGHT: 22" — 60"

Heavy-duty butyl rubber diaphragm expansion tank allows permanent separation of air and water.*

PAX Expansion Tanks

CAPACITY: 8 — 132 Gallons
(30-500 liters)

DIAMETER: 14" — 24"

HEIGHT: 25" — 85"

Heavy duty partial acceptance rubber bladder design for potable water systems.*

CBX Expansion Tanks

CAPACITY: 4 — 160 Gallons
(15-600 liters)

DIAMETER: 14" — 30"

HEIGHT: 15" — 80"

Molded rubber membrane allows permanent separation of air and hydronic system fluid. Field removable partial acceptance membrane design specifically developed for smaller heating and chilled water systems.*

PS Expansion Tanks

CAPACITY: 15 — 515 Gallons
(57-1893 liters)

DIAMETER: 14" — 36"

HEIGHT: 25" — 127"

Available in either red oxide painted or galvanized. Optional saddles for horizontal installations are available.*

CA Style
Expansion Tank



CX Style
Expansion Tank



Multi-Purpose Tank
(MPT)



Buffer Tank



PAX Style
Expansion Tank



Buffer Tanks

CAPACITY: 50 — 3000 Gallons
(189-11,356 liters)

FLANGE SIZES: 2" — 12"

DIAMETER: 20" — 84"

HEIGHT: 43" — 145"

Available in either red oxide painted or galvanized. Optional saddles for horizontal installations are available.*

Multi-Purpose Tanks (MPT)

CAPACITY: 50 — 3000 Gallons
(189-11,356 liters)

FLANGE SIZES: 2" — 12"

DIAMETER: 20" — 84"

HEIGHT: 43" — 145"

Most Taco Expansion Tanks are available with either bladders or diaphragms so that water and air are permanently separated. No absorption can take place at any point during the system cycle, and you avoid the problems of waterlogged tanks, air-bound terminal units, excessive corrosion, inefficient balancing and pump cavitations.

* Each of these tank model is fabricated in accordance with ASME Section VIII, Div. 1 to assure highest quality & performance.