



310 UNIVERSAL BEAM CLAMP, THICK FLANGE



CERTIFICATIONS



FEATURES

Universal beam clamp for thick beams

SPECIFICATIONS


Material Cast Iron

Catalog Number	Finish	Rod Size(RS)	Flange Thickness(FT)	A	Torque(TQ)	Static Load 1(F1)	Static Load 2(F2)	Packing Quantity
3100037EG	Electrogalvanized	3/8"	1 1/4" Max	1"	5 ft lb	500 lb	250 lb	1.0000
3100037PL	Plain	3/8"	1 1/4" Max	1"	5 ft lb	500 lb	250 lb	1.0000
3100050EG	Electrogalvanized	1/2"	1 1/4" Max	1"	11 ft lb	950 lb	760 lb	1.0000
3100050PL	Plain	1/2"	1 1/4" Max	1"	11 ft lb	950 lb	760 lb	1.0000

ADDITIONAL PRODUCT DETAILS

Setscrew must be tightened and torqued onto the sloped side of the I-beam.

DIAGRAMS



WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

North America

+1.800.753.9221

Option 1 – Customer Care

Option 2 – Technical Support

Europe

Netherlands:

+31 800-0200135

France:

+33 800 901 793

Europe

Germany:

800 1890272

Other Countries:

+31 13 5835404

APAC

Shanghai:

+ 86 21 2412 1618/19

Sydney:

+61 2 9751 8500



Our powerful portfolio of brands:

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

© 2022 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

nVent reserves the right to change specifications without notice.