


# Threaded Rod



- Cut to length as needed



Material: Steel  
 Finish: Electrogalvanized  
 Tensile Strength: 58,000 psi  
 Yield Strength: 36,000 psi

Part Number	Rod Size RS	Length L	Static Load F
0502506EG	1/4"	6'	240 lb
0502510EG	1/4"	10'	240 lb
0503706EG	3/8"	6'	600 lb
0503710EG	3/8"	10'	610 lb
0503712EG	3/8"	12'	600 lb
0505006EG	1/2"	6'	1,130 lb
0505010EG	1/2"	10'	1,130 lb
0505012EG	1/2"	12'	1,130 lb
0506206EG	5/8"	6'	1,810 lb
0506210EG	5/8"	10'	1,810 lb
0506212EG	5/8"	12'	1,810 lb
0507506EG	3/4"	6'	2,710 lb
0507510EG	3/4"	10'	2,710 lb
0507512EG	3/4"	12'	2,710 lb
0508706EG	7/8"	6'	3,770 lb
0508710EG	7/8"	10'	3,770 lb

Load based on Max. 650 degrees F.

**WARNING**

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.

